



FROSTED GLASS PAINT



CONSTRUCTION STEPS



1		CLEAN THE GLASS SURFACE THOROUGHLY.KEEP IT DRY. 玻璃表面处理干净,保持干燥
2		FOR PARTS A AND B, ADD THE CROSS-LINKING AGENT IN A RATIO OF 50:1 AND MIX WELL. USE THE PAINT MIXED WITH THE CROSS-LINKING AGENT WITHIN 6 HOURS A+B组份, 加入交联剂, 按50:1配比, 搅拌均匀, 油漆加入交联剂后6个小时内用完
3		APPLY THE PAINT 上漆
4		APPLY 2-3 THIN COATS, WITH EACH COAT SPACED 2-3 HOURS APART. MULTIPLE THIN COATS ARE RECOMMENDED FOR BETTER RESULTS. 薄刷2-3遍, 每遍间隔2-3小时, 薄刷多次效果更佳
5		AVOID CONTACT WITH WATER FOR 12 HOURS AFTER CONSTRUCTION. THE PAINT FILM WILL BE FULLY DRY AFTER A WEEK. DO NOT SCRATCH OR BUMP DURING THIS PERIOD. 施工完成后12小时内避免沾水, 一个星期后漆膜完全干透, 期间请勿刮擦、磕碰

IMPORTER BY
Hoongseng builder and construction sdn bhd
42, jalan industri usj 1/12, Taman perindustrian usj1, 47620, subang jaya, Selangor , Malaysia
Hotline:++60380818568

Supervised by Fujian Jishan Technology Co., Ltd.
Manufactured by Fuzhou Jishan Waterproofing Technology Co., Ltd.
Jishan Building, No. 2 Jinpu Branch Road, Cangshan Science and Technology Park, Fuzhou City, Fujian Province.
National Service Hotline: 400-600-3150

JISHAN REPAIR

FROSTED GLASS PAINT

(Material: transparent polyurea)
transparent glass frosted paint and waterproof coating

Transparent to frosted
Suitable for internal and external glass door , glass window, glass railing, glass roof
also suitable apply coating on bathroom, balcony- wall and floor tiles for repair concrete slab leaking waterproofing works
*waterproof
*anti slip
*weather resistance
*UV resistance
*anti stain



Protect privacy

Water-proof and stain-resistant

Strong adhesion

JISHAN REPAIR

FROSTED GLASS PAINT

- Protect privacy
- Water-proof and stain-resistant
- Strong adhesion



Usage method

① CLEAN Clean the glass surface thoroughly. Keep it dry.	② MIX THE PAINT Add the cross-linking agent at a ratio of 50:1 and mix well. Use the paint mixed with the cross-linking agent within 6 hours.	③ STIR Stir well.	④ APPLY THE PAINT Roller coating Brush coating	⑤ CONSTRUCTION Apply 2-3 thin coats, with each coat spaced 2-3 hours apart. Multiple thin coats are recommended for better results.	⑥ DRYING Avoid contact with water for 12 hours after construction. The paint film will be fully dry after a week. Do not scratch or bump during this period.
---	--	--------------------------	---	--	---

Precautions

- Store the product in a well-ventilated, cool, and shaded area away from direct sunlight, with a temperature range of 5-35°C.
- Do not mix this product with other paints or oil-based paints.
- Avoid contact with water and avoid bumping within 24 hours after application.
- Avoid direct fan blowing during construction or drying process.
- If the product gets into the eyes, rinse with clean water and seek medical attention promptly.
- Keep this product out of reach of children.

Reminders

- Ensure tools are dry during application. Avoid applying too thick a layer at once, as this may lead to slow drying, whitening, bubbling, and unevenness of the paint film.
- The surface drying time is 4 hours, full drying takes 48 hours, and the best results are achieved after 7 days.
- The construction temperature shall not be below 5°C, and the air humidity shall not exceed 80%.
- The product mixed with the cross-linking agent must be used within 6 hours.
- For outdoor construction, check the weather forecast for the next two days. Avoid water contact, scraping, and bumping within 24 hours.
- Generally, apply 2-3 coats, with each coat spaced at least 2 hours apart.
- The shelf life is 1 year.

Construction Conditions

 Temperature >5°C	 Humidity <80%	 No construction on rainy days
----------------------	-------------------	-----------------------------------

IMPORTER BY
Hoongseng builder and construction sdn bhd
42, jalan industri usj 1/12, Taman perindustrian usj1, 47620, subang jaya, Selangor , Malaysia
Hotline:++60380818568

Supervised by Fujian Jishan Technology Co., Ltd.
Manufactured by Fuzhou Jishan Waterproofing Technology Co., Ltd.
Jishan Building, No. 2 Jinpu Branch Road, Cangshan Science and Technology Park, Fuzhou City, Fujian Province.
National Service Hotline: 400-600-3150



JISHAN REPAIR

FROSTED GLASS PAINT

- Protect privacy
- Water-proof and stain-resistant
- Strong adhesion



使用方法

① 清理 玻璃表面处理干净 保持干燥	② 调漆 按50:1配比加入交联剂搅拌均匀, 油漆加入交联剂后6个小时内用完	③ 搅拌 搅拌均匀	④ 上漆 滚涂 刷涂	⑤ 施工 薄刷2-3遍, 每遍间隔2-3小时, 薄刷多次效果更佳	⑥ 待干 薄刷2-3遍, 每遍间隔2-3小时, 薄刷多次效果更佳
---------------------------	---	------------------	-------------------	---	---

注意事项

- 产品存储于5-35°C的通风、阴凉、避光处。
- 严禁与其它油漆或者油性漆混合使用。
- 刷涂完毕在24小时内避免沾水、磕碰。
- 在施工或待干过程中避免风扇直吹。
- 如沾染眼睛里用清水冲洗, 并及时就医。
- 请将该产品置于儿童不能触及的地方。

温馨提示

- 施工时, 需确保工具无明水, 施工不宜一道涂太厚, 否则会造成漆膜干燥慢、发白起泡、不均匀等弊端。
- 表干时间4h, 实干48小时, 效果最佳需要7天。
- 施工温度不可低于5°C, 在空气湿度不可高于80%。
- 加交联剂之后, 需在6小时内用完。
- 户外施工需查看未来两天天气预报, 24小时内不可沾水、刮蹭、磕碰。
- 一般刷涂2-3遍, 每遍间隔2小时以上。
- 保质期1年。

施工条件

 温度 > 5°C	 湿度 <80%	 雨天不施工
--------------	-------------	-----------

IMPORTER BY
Hoongseng builder and construction sdn bhd
42, jalan industri usj 1/12, Taman perindustrian usj1, 47620, subang jaya, Selangor , Malaysia
Hotline:++60380818568

Supervised by Fujian Jishan Technology Co., Ltd.
Manufactured by Fuzhou Jishan Waterproofing Technology Co., Ltd.
Jishan Building, No. 2 Jinpu Branch Road, Cangshan Science and Technology Park, Fuzhou City, Fujian Province.
National Service Hotline: 400-600-3150

