



FROSTED GLASS PAINT



CONSTRUCTION STEPS

1		CLEAN THE GLASS SURFACE THOROUGHLY. KEEP IT DRY. 玻璃表面处理干净, 保持干燥
2		FOR PARTS A AND B, ADD THE CROSS-LINKING AGENT IN A RATIO OF 50:1 AND MIX WELL. USE THE PAINT MIXED WITH THE CROSS-LINKING AGENT WITHIN 6 HOURS. A+B组份, 加入交联剂, 按50:1配比, 搅拌均匀, 油漆加入交联剂后6个小时内用完
3		APPLY THE PAINT 上漆
4		APPLY 2-3 THIN COATS, WITH EACH COAT SPACED 2-3 HOURS APART. MULTIPLE THIN COATS ARE RECOMMENDED FOR BETTER RESULTS. 薄刷2-3遍, 每遍间隔2-3小时, 薄刷多次效果更佳
5		AVOID CONTACT WITH WATER FOR 12 HOURS AFTER CONSTRUCTION. THE PAINT FILM WILL BE FULLY DRY AFTER A WEEK. DO NOT SCRATCH OR BUMP DURING THIS PERIOD. 施工完成后12小时内避免沾水, 一个星期后漆膜完全干透, 期间请勿刮擦、碰碰

IMPORTER BY
Hoongseng builder and construction sdn bhd
42, jalan industri usj 1/12, Taman perindustrian usj1, 47620, subang jaya, Selangor, Malaysia
Hotline: +60380818568

Supervised by Fujian Jishan Technology Co., Ltd.
Manufactured by Fuzhou Jishan Waterproofing Technology Co., Ltd.
Jishan Building, No. 2 Jinpu Branch Road, Cangshan Science and Technology Park, Fuzhou City, Fujian Province.
National Service Hotline: 400-600-3150



FROSTED GLASS PAINT

(Material: transparent polyurea)
transparent glass frosted paint and waterproof coating

Transparent to frosted
Suitable for internal and external glass door, glass window, glass railing, glass roof
also suitable apply coating on bathroom, balcony- wall and floor tiles for repair concrete slab leaking waterproofing works
*waterproof
*anti slip
*weather resistance
*UV resistance
*anti stain



Protect privacy

Water-proof and stain-resistant

Strong adhesion



FROSTED GLASS PAINT

- Protect privacy
- Water-proof and stain-resistant
- Strong adhesion



Usage method

① CLEAN Clean the glass surface thoroughly. Keep it dry.	② MIX THE PAINT Add the cross-linking agent at a ratio of 50:1 and mix well. Use the paint mixed with the cross-linking agent within 6 hours.	③ STIR Stir well.	④ APPLY THE PAINT Roller coating and Brush coating	⑤ CONSTRUCTION Apply 2-3 thin coats, with each coat spaced 2-3 hours apart. Multiple thin coats are recommended for better results.	⑥ DRYING Avoid contact with water for 12 hours after construction. The paint film will be fully dry after a week. Do not scratch or bump during this period.
--	---	-----------------------------	--	---	--

Precautions

- Store the product in a well-ventilated, cool, and shaded area away from direct sunlight, with a temperature range of 5-35°C.
- Do not mix this product with other paints or oil-based paints.
- Avoid contact with water and avoid bumping within 24 hours after application.
- Avoid direct fan blowing during construction or drying process.
- If the product gets into the eyes, rinse with clean water and seek medical attention promptly.
- Keep this product out of reach of children.

Reminders

- Ensure tools are dry during application. Avoid applying too thick a layer at once, as this may lead to slow drying, whitening, bubbling, and unevenness of the paint film.
- The surface drying time is 4 hours, full drying takes 48 hours, and the best results are achieved after 7 days.
- The construction temperature shall not be below 5°C, and the air humidity shall not exceed 80%.
- The product mixed with the cross-linking agent must be used within 6 hours.
- For outdoor construction, check the weather forecast for the next two days. Avoid water contact, scraping, and bumping within 24 hours.
- Generally, apply 2-3 coats, with each coat spaced at least 2 hours apart.
- The shelf life is 1 year.

Construction Conditions

Temperature > 5°C	Humidity < 80%	No construction on rainy days
-------------------	----------------	-------------------------------

IMPORTER BY
Hoongseng builder and construction sdn bhd
42, jalan industri usj 1/12, Taman perindustrian usj1, 47620, subang jaya, Selangor, Malaysia
Hotline: +60380818568

Supervised by Fujian Jishan Technology Co., Ltd.
Manufactured by Fuzhou Jishan Waterproofing Technology Co., Ltd.
Jishan Building, No. 2 Jinpu Branch Road, Cangshan Science and Technology Park, Fuzhou City, Fujian Province.
National Service Hotline: 400-600-3150



FROSTED GLASS PAINT

- Protect privacy
- Water-proof and stain-resistant
- Strong adhesion



使用方法

① 清理 玻璃表面处理干净, 保持干燥	② 调漆 按50:1配比加入交联剂搅拌均匀, 油漆加入交联剂后6个小时内用完	③ 搅拌 搅拌均匀	④ 上漆 滚涂 刷涂	⑤ 施工 薄刷2-3遍, 每遍间隔2-3小时, 薄刷多次效果更佳	⑥ 晾干 薄刷2-3遍, 每遍间隔2-3小时, 薄刷多次效果更佳
-------------------------------	--	---------------------	----------------------	--	--

注意事项

- 产品存储于5-35°C的通风、阴凉、避光处。
- 严禁与其它的油漆或者油性漆混合使用。
- 刷涂完毕在24小时内避免沾水、碰碰。
- 在施工或晾干过程中避免风扇直吹。
- 如沾染眼睛里用清水冲洗, 并及时就医。
- 请将该产品置于儿童不能触及的地方。

温馨提示

- 施工时, 需确保工具无明水, 施工不宜一道涂太厚, 否则会造成漆膜干燥慢、发白起泡、不均匀等弊病。
- 表干时间4h, 实干48小时, 效果最佳需要7天。
- 施工温度不可低于5°C, 在空气湿度不可高于80%。
- 加交联剂之后, 需在6小时内用完。
- 户外施工需查看未来两天天气预报, 24小时内不可沾水、刮碰、碰碰。
- 一般刷涂2-3遍, 每遍间隔2小时以上。
- 保质期1年。

施工条件

温度 > 5°C	湿度 < 80%	雨天不施工
----------	----------	-------

IMPORTER BY
Hoongseng builder and construction sdn bhd
42, jalan industri usj 1/12, Taman perindustrian usj1, 47620, subang jaya, Selangor, Malaysia
Hotline: +60380818568

Supervised by Fujian Jishan Technology Co., Ltd.
Manufactured by Fuzhou Jishan Waterproofing Technology Co., Ltd.
Jishan Building, No. 2 Jinpu Branch Road, Cangshan Science and Technology Park, Fuzhou City, Fujian Province.
National Service Hotline: 400-600-3150

