

**JISHAN
REPAIR**

HAND-APPLIED POLYURETHANE COVER PAINT

Applicable to add an extra layer of waterproof coating on the rc floor slab and roof tiles, metal roof, rc flat roof to extend the life of the existing waterproof layer. Also suitable for indoor and outdoor wall surfaces, tile surfaces, pebble wash surfaces- color retention, stain resistance, easy clean



High transparency

Dense paint film

Strong interlayer
adhesion

**JISHAN
REPAIR**

HAND-APPLIED POLYURETHANE COVER PAINT

High transparency Dense paint film Strong interlayer adhesion



PICC
This product is
covered by PICC

Product Description

Jishan Repair Polyurethane Cover Paint is meticulously formulated from modified acrylic ester polymer emulsion and various premium additives. It is a finishing varnish specially designed for hand-applied polyurethane waterproof coatings. The paint film features high gloss, excellent fullness, fast drying, excellent film formation, strong interlayer adhesion, and strong weather resistance and stain resistance. Due to its nanoscale particle size and low-emulsion synthesis process, the product has superlative water resistance and acid-alkali resistance, making it particularly suitable for the finishing of oil-based or water-based substrates.

Scope of Application

Applicable to the finishing of oil-based or water-based acrylic, polyurethane, epoxy, and polyurea substrates; especially applicable to the finishing of hand-applied polyurethane waterproof coatings to improve its resistance to dirt.

Features

- Single-component water-based product, environmentally friendly and easy to apply.
- Excellent water resistance and acid-alkali resistance.

Instructions for Use

- Substrate requirements: The substrate must be smooth, clean, and dry.
- Dilution ratio: Dilute with less than 10% water.
- Application methods: Brushing, rolling, or spraying.
- Cleaning method: Clean tools immediately with water after use.
- Theoretical consumption: 8-10m²/kg in one coating with a film thickness of 25 microns. The actual consumption may vary depending on the surface roughness and dilution ratio.
- Application conditions: Apply at a temperature between 5-35°C and a relative humidity below 85%. Avoid any windy or rainy days.

Precautions

- Hazards: Accidental contact with eyes, skin, or hair during application may cause eye irritation or skin allergic reactions.
- Preventive measures: Keep children and pets away from the application area and store the product out of their reach; avoid inhaling gas, smoke, vapors, or sprays; wear protective gear during use and wash hands and other contact areas after operation.
- Accident response: If skin or hair is contaminated, rinse with plenty of soapy water and clean water. If eyes are contaminated, immediately rinse with plenty of clean water and seek medical help. If skin irritation or rash occurs, seek medical attention promptly.
- Safe storage: Store in a cool, dry place at temperatures between 5°C and 35°C, away from direct sunlight, and keep containers tightly sealed. Store separately from strong acids, alkalis, oxidizers, food, and animal feed. Do not pour diluted paint back into the original package. Use promptly after opening.
- Shelf life: The shelf life is 12 months from the production date as indicated on the product certificate.
- Waste disposal: Please dispose of discarded paints by following national and local regulations (refer to the Safety Technical Manual before disposal).

Standards

HG/T 5065-2016 (coating)

Statement

Please follow the instructions in the user manual for proper construction. We will not be held responsible for any losses resulting from your improper use. For any inquiries, please consult your local dealer or our technical service department.

IMPORTER BY

Hoongseng builder and construction sdn bhd
42, jalan industri usj 1/12, Taman perindustrian usj1, 47620, subang jaya, Selangor, Malaysia
Hotline: +60380818568

Supervised by Fujian Jishan Technology Co., Ltd.

Manufactured by Fuzhou Jishan Waterproofing Technology Co., Ltd.

Jishan Building, No. 2 Jinpu Branch Road, Cangshan Science and Technology Park, Fuzhou City, Fujian Province.
National Service Hotline: 400-600-3150

