

**JISHAN
REPAIR**

HIGHLY VISCOUS TILES ADHESIVE

Applicable to all kinds of wall and floor tiles to prevent tiles popping out and falling off. *Not suitable for oversized tiles (2x4ft tiles) and tiles that have been soaked in water for a long time



- Strong penetration
- Long-lasting adhesion

- Strong water resistance
- Strong bonding force

**JISHAN
REPAIR**

HIGHLY VISCOUS TILES ADHESIVE

- Strong penetration
- Long-lasting adhesion
- Strong water resistance
- Strong bonding force

PCC
This product is covered by PCC



Basic Introduction

Jishan Repair Highly Viscous Tile Adhesive is a single-component water-based product, characterized by its eco-friendliness, ease of use, pressure sensitivity, and excellent bonding properties. This adhesive can absorb the stress generated by slight movements between the substrate and ceramic tiles. Its high pressure sensitivity ensures a synergistic bonding effect between the cured tile adhesive and the film achieved through chemical cross-linking and physical anchoring, which can effectively prevent the occurrence of hollow or detached tiles.

Precautions

- Once opened, the product should be used up as soon as possible. The container should be immediately sealed with the lid after being opened. When the application is completed or stopped mid-way, cleaning agents should be used to clean the tools, which should be maintained in good condition during the application process.
- This product should be kept dry during transportation, storage, and use, and should never be left uncovered in the open air.
- During application, please take necessary safety measures. Wear a mask and goggles to prevent the material from contacting the operator's body.

Scope of Application

This product is applicable to the paving of ceramic tiles, stone, and other finishing materials on stable indoor surfaces. For large tiles or floor tiles, two-component large plate adhesive is recommended.

Instructions for Use

- The operable temperature is between 5°C and 40°C. Please stir well before use after opening the container.
- Any mold release agent, dust, oil stains, or other impurities on the back of tiles must be thoroughly removed.
- Apply the adhesive evenly onto the pre-treated surface (such as the back of the tile).
- For the optimal adhesion result, after applying the adhesive, let it dry until it turns transparent and then use tile adhesive.
- The product must fully cover the back of ceramic or stone tiles without any missed area.
- Painted ceramic tiles should be placed flat with the back facing up to avoid dust, debris, or other particles from sticking to the surface and affecting the adhesion.

Standard

T/CBMF 87-2020

Packaging and Storage

- This product should be packaged and transported in sealed containers as a general chemical building material. During transportation, precautions should be taken to avoid exposure to sunlight and rain, prevent squeezing and collisions, and ensure the packaging remains intact.
- The package must be stored and transported in an upright position and in a cool, dry place between 5°C and 35°C.
- Shelf life: 12 months

Statement

Please follow the instructions in the user manual for proper construction. We will not be held responsible for any losses resulting from your improper use. For any inquiries, please consult your local dealer or our technical service department.

IMPORTER BY

Hoongseng builder and construction sdn bhd

42, Jalan Industri usj 1/12, Taman perindustrian usj1, 47620, subang jaya, Selangor, Malaysia
Hotline: +60350818568

Supervised by Fujian Jishan Technology Co., Ltd.

Manufactured by Fuzhou Jishan Waterproofing Technology Co., Ltd.

Jishan Building, No. 2 Jinpu Branch Road, Cangshan Science and Technology Park, Fuzhou City, Fujian Province.
National Service Hotline: 400-600-3150



6 975732 261972

